

Technical parameters		WFT 13	WFT 15
Diameter of Spindle	mm in	130 5.12"	150 5.91"
Taper of Spindle		ISO-50 / BT-50 CAT-50	
Range of Spindle speed	rpm	3 000/4 000	
Rated Power of Main Engine S1/S6	kW HP	up to 53/64 71/86	
Travel Table X	mm in	2 000 / 3 000 / 4 000 / 5 000 78.74"/118.11"/157.48"/196.85"	
Headstock Vertical Travel Y	mm in	2 000 / 2 500 / 3 000 / 3 500 78.74" /98.43"/118.11"/137.80"	
Longitudinal Travel Z	mm in	1 500 / 2 000 59.05"/ 78.74"	2 100 / 3 300 82.68"/ 129.92"
Extension Spindle Travel W	mm in	730 28.74"	1 000 39.37"
Longitudinal Headstock Travel V (WFT 13R)	mm in	700 27.60"	
Operating Feed X, Y, Z, W, (V)	mm/min in min	max. 8 000 315"	
Operating Feed B	rpm	max. 2	
Rapid Traverse X, Y	mm/min in min	12 000 / 28 000 * 472.44" /1002.36" *	
Rapid Traverse Z / W	mm/min in min	10 000 393.70"	
Max. Table Load	kg lb	see page 43	
Table Dimensions	mm in	see page 43	

* For WFT Linear