

Linmax B Specifications

Machine specification

Specifications /Mold	Unit	Linmax B-22	Linmax B-25	Linmax B-30	Linmax B-35	Linmax B-40
X-axis (Longitudinal)	mm	3200/4000 (or more)	4000/5000 (or more)	5000/6000 (or more)	5000/6000 (or more)	6000/8000 (or more)
Y-axis (Cross)	mm	2200	2500	3000	3500	4000
Z-axis (Vertical)	mm	1250	1250	1250	1250	1250
Table long	mm	3200/4000 (or more)	4000/5000 (or more)	5000/6000 (or more)	5000/6000 (or more)	6000/8000 (or more)
Table load	Kg/m ²	5000				
Distance between spindle nose	mm	200-1450	200-1450	200-1450	200-1450	200-1450
Distance between column	mm	3290	3590	4090	4590	5090

Feed rate

X/Y/Z-axis rapid feed rate	m/min	60 / 60 / 50				
----------------------------	-------	--------------	--	--	--	--

Automatic Tool Changer

Milling Head Type	Unit	TCH-20 (A63)	TCH-19 (A63)	TCH-19 (A100)	TCH-20 (A100)	TCH-100A
Tool shank	type	HSK A63		HSK A100		
Tool magazine capacity / opt	Pcs	30 / 60		30 / 60		
Max. tool weight	Kgs	8		15		
Max. tool length	mm	350		350		
Max. tool dimensions	mm	Ø 75		Ø 125		

The Company reserves the right to change, with all the technical specifications of the contract-based technology.